

NASA TECH BRIEF



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Division, NASA, Code UT, Washington, D.C. 20546.

High-Strength Magnetic Materials




Figure 1. Magnetic Induction Versus Temperature

Two new high-strength magnetic alloys have been developed which are suitable for operation in the 800° to 1600° F range: a new class of precipitation-hardened maraging steels designated martensitic alloy 1-A-S-2, and a precipitation-hardened cobalt base alloy, 1-B-S-1. Typical composition (in weight %) of the new martensitic alloy is (Fe-12Ni-30Co-1W-3Ta-0.04Al-0.4Ti), and of the cobalt-based alloy is (Co-5Fe-15Ni-1.2Al-5.0Ta-0.2Zr).

The martensitic alloy has higher temperature capabilities than the comparable commercial alloy, modified H-11 tool steel (Fe-5Cr-1Mo-1V) and is considered to be a possible replacement for it. (See Figure 1. Magnetic Induction Versus Temperature—at a magnetization of 250 to 300 oersteds for high-temperature magnetic alloys developed in this program compared to existing alloys.) The precipitation-hardened cobalt-base alloy has greatly improved creep resistance over

(continued overleaf)

- 15% Ni Maraging Steel (100-Hour data)
 - △ Iron 27% Cobalt Magnetic Alloy (1000-Hour Data) (Reference)
 - ◇ Modified H-11 Tool Steel (2000-Hour Data) (Reference Martensitic Alloy)
 - ◆ New PH Martensitic Alloy (est)*; Proposed Replacement for the above Alloys
 - (Co-23Ni-1.7Ti-0.4Al-0.2Zr) Alloy (5000-10,000 Hour Data) (Reference Cobalt Alloy)
 - ▽ New PH Cobalt Alloy 1-B-S-1 (1000-Hour Data); Proposed Replacement for the above Alloy
- *Extrapolation of 1000-Hour Data




Figure 2. Stress to produce 0.4 percent creep strain in 10,000 hours based upon extrapolations using the Larson-Miller parameter.

that of the best comparable commercial alloy, (Co-23 Ni-1.7Ti-0.4Al-0.2Zr) and is considered to be a possible replacement. (See Figure 2. Comparison is made between alloys developed on this program and commercially available alloys.) These new alloys have application in high-temperature inductors and alternators where creep resistance and magnetic induction govern the weight of a generator.

Notes:

1. The following documentation may be obtained from:

Clearinghouse for Federal Scientific
and Technical Information
Springfield, Virginia 22151
Single document price \$3.00
(or microfiche \$0.65)

Reference:

NASA CR-1460 High Temperature (800° to 1600°F) Magnetic Materials

2. Technical questions may be directed to:

Technology Utilization Officer
Lewis Research Center
21000 Brookpark Road
Cleveland, Ohio 44135
Reference: B70-10596

Patent status:

Title to this invention has been waived under the provisions of the National Aeronautics and Space Act [42 U.S.C. 2457(f)], to the Westinghouse Electric Corporation, Wapak Road, Lima, Ohio.

Source: K. Detert of
Westinghouse Electric Corporation
under contract to
Lewis Research Center
(LEW-10697)